





# Throttling butterfly valve, DeviceNet<sup>TM</sup> controller

HV throttling butterfly valve, DN 63 ISO, QPDG controller, 24 VDC, SS

Part number: TBVQPDNG-L063






### Throttling butterfly valve, DeviceNet<sup>™</sup> controller HV throttling butterfly valve, DN 63 ISO, QPDG controller, 24 VDC, SS

- Adaptive algorithm for improved stability and faster transitions
- Space saving, low cost design
- High reliability, low particle generation
- Can be operated in any orientation
- Body can be heated up to 200°C with optional heaters
- CE marked/fully REACH and RoHS compliant



Similar Image



#### **TBVQPDNG-L063**

Parameters	Specifications
Valve / Flange Size	DN 63 ISO-F
Communications Interface	DeviceNet™
Additional Controller Features	Gauge Supply
Flange Size / Type	DN 63 ISO-F
Controller Communications	DeviceNet™ system interface; RS232 service port
Supply Voltage	24 V DC (±5 %)
Power Connector	XLR, 5-pin, Female
Gauge Power Supply	±15 V DC (±5%), 1.4 A max.
Pressure Range	1 · 10 <sup>-8</sup> mbar to 1.1 bar
Max Differental at Opening	1100 mbar
Max Temp (body)	150 °C

Dimensions (in inches)	
Dim A	5.12"
Dim B	4.33"
Dim C	0.354"
Dim D	2.43"
Dim E	1.00"
Dim F	11.7"
Dim G	9.09"
Dim H	6.22"
Dim J-1	2.17"
Dim J-2	2.36"
Dim K	2.76"
Dim L	2.36"
Bolt Hole Dia.	0.359"
# Bolt Holes	4

www.n-c.com Part number: TBVQPDNG-L063 NC0721A Page 2



## Throttling butterfly valve, DeviceNet<sup>™</sup> controller HV throttling butterfly valve, DN 63 ISO, QPDG controller, 24 VDC, SS

#### **TBVQPDNG-L063**

Parameters (Continued)	Specifications (Continued)
Temp. Limits (actuator)	5 °C (minimum), 45 °C (maximum)
Open / Close Time	125 ms/125 ms
Open Conductance	380 l/s
Min. Control Conductance	0.5 l/s
Material (valve body)	316L Stainless Steel
Material (valve mechanism)	316L Stainless Steel
Plate Seal	none
Shaft Seal	FKM
Leak Rate (body)	1 · 10 <sup>-9</sup> mbar l/s
Service Life	5 million cycles
Weight	7.7 lbs

www.n-c.com Part number: TBVQPDNG-L063 NC0721A Page 3

#### **VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH**

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

#### **EARNING YOUR TRUST**

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

#### **INNOVATION SINCE 1962**

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products Headquarters: USA 1-800-824-4166 or 530-842-4457 ncsales@n-c.com www.n-c.com



RoHS2/REACH compliant Conflict mineral regulations enforced



