



Similar Image



HV throttling pendulum valve, Analog/TTL controller

DN 160 ISO-F, Analog controller, hard anodized finish, 24 V DC ($\pm 5\%$)

Part number: TPVQPANG-H103

HV throttling pendulum valve, Analog/TTL controller DN 160 ISO-F, Analog controller, hard anodized finish, 24 V DC ($\pm 5\%$)

- Adaptive algorithm for improved stability and faster transitions
- Space saving, low cost design
- High reliability, low particle generation
- Can be operated in any orientation
- Body can be heated up to 120°C with optional heater jackets
- CE marked/fully REACH and RoHS compliant



Similar Image



Dimensions (in inches)

Dim A	3.46"
Dim B	3.31"
Dim C	20.5"
Dim D	13.5"
Dim E	7.64"
Dim F	11.1"
Dim G	7.87"
Dim H	5.31"
Bolt Hole Thread	M10
Thread Depth	0.394"
# Bolt Holes	8

TPVQPANG-H103

Parameters	Specifications
Valve / Flange Size	DN 160 ISO-F
Communications Interface	Analog
Finish	Hard Anodized
Additional Controller Features	Gauge Supply
Flange Size / Type	DN 160 ISO-F
Controller Communications	Analog/TTL system interface; RS232 service port
Supply Voltage	24 V DC ($\pm 5\%$)
Power Connector	XLR, 5-pin, Female
Gauge Power Supply	± 15 V DC ($\pm 5\%$), 1.4 A max.
Power Fail Option	not included
Pressure Range	$3.8 \cdot 10^{-8}$ mbar to 1.1 bar

HV throttling pendulum valve, Analog/TTL controller
DN 160 ISO-F, Analog controller, hard anodized finish, 24 V DC ($\pm 5\%$)

TPVQPANG-H103

Parameters <i>(Continued)</i>	Specifications <i>(Continued)</i>
Max Differential at Opening	27 mbar
Max Temp (body)	150 °C
Temp. Limits (actuator)	5 °C (minimum), 45 °C (maximum)
Open / Close Time	3.3 s/2.8 s
Open Conductance	5000 l/s
Min. Control Conductance	0.1 l/s
Material (valve body)	6061-T6 Aluminum, Hard anodized
Material (valve mechanism)	304 Stainless & 6061-T6 Aluminum, Hard anodized
Gate Seal	FKM
Bonnet Seal	FKM
Leak Rate (body)	$1 \cdot 10^{-9}$ mbar l/s
Leak Rate (gate)	$1 \cdot 10^{-6}$ mbar l/s
Service Life	1 million cycles
Weight	39.82 lbs

VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

EARNING YOUR TRUST

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

INNOVATION SINCE 1962

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products

Headquarters: USA

1-800-824-4166 or 530-842-4457

nccsales@n-c.com

www.n-c.com



RoHS2/REACH compliant
Conflict mineral regulations enforced

All data subject to change without prior notice.

Nor-Cal Products



by PFEIFFER VACUUM