



Similar Image



HV throttling pendulum valve, DeviceNet™ controller

**DN 320 ISO-F, DeviceNet™ controller, bright dipped finish,
24 V DC ($\pm 5\%$)**


Part number: TPVQPDBN-C133

HV throttling pendulum valve, DeviceNet™ controller DN 320 ISO-F, DeviceNet™ controller, bright dipped finish, 24 V DC (±5 %)

- Adaptive algorithm for improved stability and faster transitions
- Space saving, low cost design
- High reliability, low particle generation
- Can be operated in any orientation
- Body can be heated up to 120°C with optional heater jackets
- CE marked/fully REACH and RoHS compliant



Similar Image



Dimensions (in inches)

| | |
|------------------|--------|
| Dim A | 4.84" |
| Dim B | 4.09" |
| Dim D | 22.8" |
| Dim E | 12.0" |
| Dim F | 11.7" |
| Dim G | 15.6" |
| Dim H | 10.6" |
| Bolt Hole Thread | M12 |
| Thread Depth | 0.709" |
| # Bolt Holes | 12 |

TPVQPDBN-C133

| Parameters | Specifications |
|--------------------------------|---|
| Valve / Flange Size | DN 320 ISO-F |
| Communications Interface | DeviceNet™ |
| Finish | Bright Dipped |
| Additional Controller Features | Power Fail Option |
| Flange Size / Type | DN 320 ISO-F |
| Controller Communications | DeviceNet™ system interface; RS232 service port |
| Supply Voltage | 24 V DC (±5 %) |
| Power Connector | XLR, 5-pin, Female |
| Gauge Power Supply | not included |
| Power Fail Option | included |
| Pressure Range | $3.8 \cdot 10^{-8}$ mbar to 1.1 bar |

HV throttling pendulum valve, DeviceNet™ controller
DN 320 ISO-F, DeviceNet™ controller, bright dipped finish, 24 V DC (±5 %)

TPVQPDBN-C133

| Parameters <i>(Continued)</i> | Specifications <i>(Continued)</i> |
|-------------------------------|-----------------------------------|
| Max Differential at Opening | 39 mbar |
| Max Temp (body) | 150 °C |
| Temp. Limits (actuator) | 5 °C (minimum), 45 °C (maximum) |
| Open / Close Time | 6.5 s/5.5 s |
| Open Conductance | 30000 l/s |
| Min. Control Conductance | 0.1 l/s |
| Material (valve body) | A356 Aluminum |
| Material (valve mechanism) | 304 Stainless & 6061-T6 Aluminum |
| Gate Seal | FKM |
| Bonnet Seal | FKM |
| Leak Rate (body) | 1 · 10 ⁻⁹ mbar l/s |
| Leak Rate (gate) | 1 · 10 ⁻⁹ mbar l/s |
| Service Life | 1 million cycles |
| Weight | 123.2 lbs |

VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

EARNING YOUR TRUST

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

INNOVATION SINCE 1962

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products

Headquarters: USA

1-800-824-4166 or 530-842-4457

nccsales@n-c.com

www.n-c.com



RoHS2/REACH compliant
Conflict mineral regulations enforced

All data subject to change without prior notice.

Nor-Cal Products



by PFEIFFER VACUUM