



# HV throttling pendulum valve, RS-232 controller

DN 350 JIS, RS232 controller, bright dipped finish, 24 V DC (±5%)

Part number: TPVQPNN-C149






### HV throttling pendulum valve, RS-232 controller DN 350 JIS, RS232 controller, bright dipped finish, 24 V DC (±5 %)

- Adaptive algorithm for improved stability and faster transitions
- Space saving, low cost design
- High reliability, low particle generation
- Can be operated in any orientation
- Body can be heated up to 120°C with optional heater jackets
- CE marked/fully REACH and RoHS compliant



Similar Image



Dimensions (in inches)	
Dim A	4.92"
Dim B	4.02"
Dim E	12.8"
Dim F	11.2"
Dim G	16.5"
Dim H	12.2"
Bolt Hole Thread	M12
Thread Depth	0.709"
# Bolt Holes	12

#### **TPVQPNN-C149**

II VQI IVIV-CITS	
Parameters	Specifications
Valve / Flange Size	DN 350 JIS
Communications Interface	RS232
Finish	Bright Dipped
Additional Controller Features	none
Flange Size / Type	DN 350 JIS
Controller Communications	RS232 system interface; RS232 service port
Supply Voltage	24 V DC (±5 %)
Power Connector	XLR, 5-pin, Female
Gauge Power Supply	not included
Power Fail Option	not included
Pressure Range	3.8 · 10 <sup>-8</sup> mbar to 1.1 bar

www.n-c.com Part number: TPVQPNN-C149 NC0721A Page 2



## HV throttling pendulum valve, RS-232 controller DN 350 JIS, RS232 controller, bright dipped finish, 24 V DC (±5 %)

#### **TPVQPNN-C149**

Parameters (Continued)	Specifications (Continued)
Max Differental at Opening	39 mbar
Max Temp (body)	150 °C
Temp. Limits (actuator)	5 °C (minimum), 45 °C (maximum)
Open / Close Time	6.5 s/5.5 s
Open Conductance	43000 l/s
Min. Control Conductance	0.1 l/s
Material (valve body)	A356 Aluminum
Material (valve mechanism)	304 Stainless & 6061-T6 Aluminum
Gate Seal	FKM
Bonnet Seal	FKM
Leak Rate (body)	1 · 10 <sup>-9</sup> mbar l/s
Leak Rate (gate)	1 · 10 <sup>-9</sup> mbar l/s
Service Life	1 million cycles
Weight	142.78 lbs
Leak Rate (body) Leak Rate (gate) Service Life	1 · 10 <sup>-9</sup> mbar l/s 1 · 10 <sup>-9</sup> mbar l/s 1 million cycles

www.n-c.com Part number: TPVQPNN-C149 NC0721A Page 3

#### **VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH**

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

#### **EARNING YOUR TRUST**

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

#### **INNOVATION SINCE 1962**

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products Headquarters: USA 1-800-824-4166 or 530-842-4457 ncsales@n-c.com www.n-c.com



RoHS2/REACH compliant Conflict mineral regulations enforced



