

Similar Image



# ASA nonrotatable flange 9" OD X 6" ID nonrotatable ASA flange w/groove

Part number: ASA-9-600N-G






## ASA nonrotatable flange 9" OD X 6" ID nonrotatable ASA flange w/groove

- One each flat and grooved flange is needed to complete a connection
- All products are available with both genders or a combination
- Contact us at 800-824-4166 if you can't find exactly what you need



Similar Image



Dimensions (in inches)	
Dim A	9.00"
Dim B	0.500"
Dim C	5.88"
Dim D	6.02"
Dim E	0.250"
Dim F	7.50"
Dim G	0.750"

#### ASA-9-600N-G

Parameters	Specifications
Flange Size	DN 4 (9" OD)
Туре	Non-rotatable
Gender	with Groove
Material	304 stainless
Bore	5.88"
Thickness	0.500"
Bolt Circle	7.50"
Bolt Hole Diameter	0.750"
# Bolt Holes	8
Vacuum Range	1 · 10 <sup>-8</sup> mbar to 1 bar
Temperature Range	-20 °C to 150 °C
Weight	4.8 lbs

www.n-c.com Part number: ASA-9-600N-G NC0721A Page 2

# **VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH**

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

# **EARNING YOUR TRUST**

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

### **INNOVATION SINCE 1962**

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products Headquarters: USA 1-800-824-4166 or 530-842-4457 ncsales@n-c.com www.n-c.com



RoHS2/REACH compliant Conflict mineral regulations enforced



