





ISO-F blank nonrotatable flange ISO-80 blank nonrotatable flange

Part number: ISO-80-000N





ISO-F blank nonrotatable flange ISO-80 blank nonrotatable flange

- ISO-K and ISO-F flanges are manufactured in accordance with DIN 28404 and ISO 1609
- Most common standard lengths and sizes listed
- Many others available
- Contact us at 800-824-4166 if you can't find exactly what you need



Dimensions (in inches)			
Dim A	5.71″		
Dim B	0.470″		
Dim C	blank		
Dim F	4.92″		
Dim G	0.359"		

Si	mi	lar	Im	an	ρ
		iui		uy	0

ISO-80-	000N
---------	------

Parameters	Specifications
Flange Size	DN 80 ISO-F
Туре	Blank
Material	304 stainless
Bore	blank
Thickness	0.470"
Bolt Circle	4.92"
Bolt Hole Diameter	0.359″
# Bolt Holes	8
Vacuum Range	FKM: 1 · 10 ⁻⁸ mbar to 1 bar Metal seal: 1 · 10 ⁻¹⁰ mbar to 1 bar
Temperature Range	FKM: -20 °C to 180 °C Metal seal: -270 °C to 150 °C
Weight	3.4 lbs

VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

EARNING YOUR TRUST

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

INNOVATION SINCE 1962

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products Headquarters: USA 1-800-824-4166 or 530-842-4457 ncsales@n-c.com www.n-c.com



RoHS2/REACH compliant Conflict mineral regulations enforced

