



# ISO-KF PVC flexible hose NW-40 PVC flexible hose, 36" length


Part number: PVC-150-36-2NW






# ISO-KF PVC flexible hose NW-40 PVC flexible hose, 36" length

- Dampen out pump vibrations with a flex coupling
- Easily join two mis-aligned ports using a flex hose
- Thin, medium and thick wall hoses offer a range of flexibility and robustness
- Standard lengths and flange combinations offered. Others available.
- Contact us at 800-824-4166 if you can't find exactly what you need





Dimensions (in inches)	
Dim A	36"
Dim B	6"
Dim C	1-1/2"
Dim D	2.00"

### PVC-150-36-2NW

Parameters	Specifications
Flange Size	DN 40 ISO-KF
Type	PVC Flexible Hose
ID	1-1/2"
Length	36"
Bend Radius	6"
Hose Material	PVC
Flange & Cuff Material	304 stainless
Vacuum Range	1 · 10 <sup>-2</sup> mbar to 1 bar
Temperature Range	-4 °C to 65 °C
Weight	0 lbs

# **VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH**

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

# **EARNING YOUR TRUST**

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

# **INNOVATION SINCE 1962**

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products Headquarters: USA 1-800-824-4166 or 530-842-4457 ncsales@n-c.com www.n-c.com



RoHS2/REACH compliant Conflict mineral regulations enforced



