

Similar Image



# CF blank wire seal flange 19" wire seal flange, blank, female

Part number: WS-19-000F






# CF blank wire seal flange

19" wire seal flange, blank, female

- Wire Seal make UHV seals possible in very large flange sizes
- Robust seal tolerant of bakeout to 450C
- Dished shape blanks and other options available
- Contact us at 800-824-4166 if you can't find exactly what you need





Similar Image

#### WS-19-000F

Parameters	Specifications
Flange Size	DN 16 (19" OD)
Type	Blank
Gender	Female
Material	304 stainless
Bore	blank
Thickness	1.31"
Bolt Circle	17.9"
Bolt Hole Diameter	0.531"
# Bolt Holes	36
Vacuum Range	1 · 10 <sup>-13</sup> mbar to 1 bar
Temperature Range	-200 °C to 450 °C
Weight	114 lbs

Dimensions (in inches)		
Dim A	19.6"	
Dim B	1.31"	
Dim C	blank	
Dim F	17.9"	
Dim G	0.531"	

www.n-c.com Part number: WS-19-000F NC0721A Page 2

# **VACUUM SOLUTIONS FOR INDUSTRY & RESEARCH**

Nor-Cal Products is a premier global source for custom and standard high and ultra-high vacuum chambers and components critical to the success of industrial, semiconductor, coating, analytics, and research applications. We offer an extensive selection of vacuum line fittings, hardware, valves and components which complement our custom manufacturing capabilities.

# **EARNING YOUR TRUST**

Innovative engineering, precision manufacturing, exceptional service and expert technical support are cornerstones of our corporate culture and continuous improvement goals. Your trust is our most important asset.

### **INNOVATION SINCE 1962**

An added value to working with Nor-Cal Products is how we apply our vacuum science and industry expertise to your production and research goals and timelines. We continue to develop new component lines and services to serve the demands of the exciting and ever emerging applications that require vacuum components.

Nor-Cal Products Headquarters: USA 1-800-824-4166 or 530-842-4457 ncsales@n-c.com www.n-c.com



RoHS2/REACH compliant Conflict mineral regulations enforced



